


## Data Sheet

**Type Number** ..... 6620  
**Designation IEC** ..... CR 1620  
**System** ..... Li-Manganese dioxide / Organic Electrolyte

**UL Recognition:**..... MH 13654 (N)  
**Nominal Voltage** ..... 3 V  
**Typical Capacity C** ..... 70 mAh  
 Load 20 kOhm, at 20°C down to 2 V



**Weight (approx.)** ..... 1,2 g  
**Volume** ..... 0,4 ccm  
**Coding**..... Date of Manufacturing Month/Year

### Temperature Ranges

Storage .....	min	max.
Discharge .....	-55°C	70°C
	-20°C	65°C

### Dimensions

Diameter (A) .....	min	max.
Height (B) .....	15,7	16,0
Shoulder Diameter[E].....	1,8	2,0
Shoulder Height [C].....	12,9	
	0,2	

**Segment** .....  
 Electronic

**Main Applications** .....  
 Watch  
 Photo  
 Electronic Devices

### Typical Capacities (at 20°C)

Discharge Type	Load	End Voltage:	2.0 V
Continuous 24h/d, 7d/w Current [µA]:	20000 Ω	Time: Capacity [mAh]: Energy [mWh]:	500 h 70 200

All Data contained herein is for single cells

For battery applications, performance data may vary from single cell data, depending on specific battery configuration

VARTA Microbattery GmbH, Daimlerstr. 1, D-73479 Ellwangen/Jagst  
 Tel.: (+49) 7961/921-0, Telefax: (+49) 7961/921-553

Subject to change without prior notice!  
 Date of issue: 2004-12-16