

**CARACTERISTIQUES ELECTRIQUES
ELECTRICAL CHARACTERISTICS**

Type	Rechargeable lithium button
IEC Designation	LIR2450
Plot / Top	-
Tension nominale / Nominal voltage	3.7V
Tension mini en décharge / Mini discharge voltage	2.75V
Charge standard 4h	<60mA at 4.2V (0.5C)
Capacité nominale / Nominal Capacity	120 mAh
Capacité mini / Minimal Capacity	100 mAh
Courant de décharge maxi / Max continuous discharge current	<180 mA (1.5C)
Cycle life at 80% DOD (0,5C)	> 500 (IEC standard)
Resistance Interne / Internal Impedance (at 1000hz)	< 300 mOhms
Température d'usage / Ambient temperature	Charge / Charging 0 to 45°C Décharge / Discharging -20° to 60°C
Temperature de stockage / Storage temperature	-20 to 40°C (Humidity: 65 ± 20%)
Charge de maintient / Trickle charge	(0.05C)~(0.1C)

**CARACTERISTIQUES PHYSIQUES
PHYSICAL CHARACTERISTICS**

Accumulateur / Battery	
Dimension (mm)	24.5 x 5 (+/- 1)
Poids / Weight (g.)	5.5

