



**CARACTERISTIQUES ELECTRIQUES  
ELECTRICAL CHARACTERISTICS**

<b>Type</b>		Rechargeable Nickel Metal Hydride
<b>IEC Designation</b>		AA
<b>Plot / Top</b>		Flat top
<b>Tension nominale / Nominal voltage</b>		1.2V
<b>Tension mini en décharge / Mini discharge voltage</b>		1V
<b>Charge standard 16h</b>		200 mA
<b>Capacité nominale / Nominal Capacity</b>		2050 mAh
<b>Capacité mini / Minimal Capacity</b>		2000 mAh
<b>Cycle life at 80% DOD (0,5C)</b>		> 500 (IEC standard)
<b>Resistance Interne / Internal Impedance (at 1000hz)</b>		< 40 Ωohms
<b>Température d'usage / Ambient temperature</b>	<b>Charge / Charging</b>	0 to 45 °c
	<b>Décharge / Discharging</b>	-20 to 60 °c
<b>Temperature de stockage / Storage temperature</b>		-20 to 45 °c (Humidity: 65 ± 20 %)
<b>Charge rapide / Fast charge</b>		up to 1000mA - Δ V=0-5mV/Cell
<b>Charge de maintient / Trickle charge</b>		(0.05C)~(0.1C)

**CARACTERISTIQUES PHYSIQUES  
PHYSICAL CHARACTERISTICS**

<b>Accumulateur / Battery</b>	
<b>Dimension (mm)</b>	49.5 x 14.5 (+/- 1)
<b>Poids / Weight (g.)</b>	28

