



SHENZHEN FEST TECHNOLOGY CO., LTD  
SHENZHEN E-YOUNG TECHNOLOGY CO., LTD (HK)

TEL: 86-755-89304183 FAX: 86-755-89304183 WEBSITE: [WWW.EFESTPOWER.COM](http://WWW.EFESTPOWER.COM)  
Address: 7E#3 Building, Chengxinhuating, Shifu Road 118, Buji, 518112, Shenzhen, China

Efest 18650 2000 mAh 3.7V rechargeable battery (Nipple)

Size	weight:	52g	Length:	48.89 mm	Diamter:	18.19mm
Info	top:	Nipple	Bottom:	non-procted		
Capacity	Typical Capacity:		(0.2C) 2200mAh		Min capacity:	(0.2C)2200mAh
Max discharge current	66000mA		max charge current		2200mA	
Max continuous discharge current	66000mA		momentary discharge current		66000mA	
Battery WH	189WHKg		max discharge rate:		10C	
Voltage:	3.7V		discharge cut-off voltage		3.0V	
Full charge voltage:	4.2V		cycle life:		0.5C 300 times	
Current	0.2C	0.5C	1C	5C	10C	
Capacity	2238	2190	2162	1952	1702	
Voltage	2.999	2.998	2.999	2.997	2.997	
Inner Resistance	39	39	39	39	37	
Temperature:	dishcharge temperature range: $-10^{\circ}\text{C}$ — $60^{\circ}\text{C}$ shcharge temperature range: $0^{\circ}\text{C}$ — $40^{\circ}\text{C}$ storage: 1 year: $-20^{\circ}\text{C}$ — $25^{\circ}\text{C}$ 3 months: $-20^{\circ}\text{C}$ — $45^{\circ}\text{C}$ 1 month: $-20^{\circ}\text{C}$ — $60^{\circ}\text{C}$					

