



AMN0652



For use in	Icom IC-F3/F4/S/T2A/A4
Replacement for	BP-196
<u>MECHANICAL CHARACTERISTICS</u>	
Dimension	57.8 X 17.6 X133.6 mm (2.27 X 0.69 X 5.26 inch)
Weight	Approx. 260g
Plastic Material	ABS
<u>ELECTRICAL CHARACTERISTICS</u>	
Chemistry	Ni-Cd
Nominal Voltage	9.6V
Nominal Capacity	1100mAh
Cell Type	SANYO KR-1100AAU
Charging Voltage	11.2V ~ 15.2V
Charging Current	0.2 ~ 2C
Discharging Current	0.2 ~ 2C
Discharge end voltage	8.0V
Temperature	Charge: $\pm 0 \sim +45 \text{ }^{\circ}\text{C}$ ($+32 \sim +113 \text{ }^{\circ}\text{F}$)
	Discharge: $-20 \sim +60 \text{ }^{\circ}\text{C}$ ($-4 \sim +140 \text{ }^{\circ}\text{F}$)
Storage:	Short Period: $-30 \sim +50 \text{ }^{\circ}\text{C}$ ($-22 \sim +122 \text{ }^{\circ}\text{F}$)
	Long Period: $-30 \sim +35 \text{ }^{\circ}\text{C}$ ($-22 \sim +95 \text{ }^{\circ}\text{F}$)