

# **ODP-AGMDINB** (629-DIN B-1300)

# **Technical Data Sheet**

# **Battery Type**

AGM with Thin Plate Pure Lead (TPPL). Advanced dual-purpose battery for engine start and deep-cycle use

### **Power & Performance**

Voltage	12V
Capacity (20-hour rate)	170Ah
Capacity (10-hour rate)	153Ah
Cold Cranking Amps (CCA, SAE J537)	1300A
PHCA - 5-second pulse current	2400A
HCA	1747A
MCA	1549A
Reserve capacity	370 mins

Short circuit current (using IEC method) Internal resistance at 20°C (using IEC method)

# **Dimensions & Weight**

Length	518 mm
Width	223 mm
Height (to top of terminals)	218 mm
Height Container	210 mm
Weight	53.2 kg

## **Temperature**

Operating Temperature Range	-40°C to +50°C
Optimum Storage Temperature	+20°C

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

# **Charging & self-discharge**


Type of charging curve	100
Charge voltage @+20°C	14.4V to 14.8V
Self-discharge per month at +20°C	1.25%
Self-discharge per month at +40°C	5%


# Fitting, handling & storage


Can be mounted or stored in any orientation except inverted. 2-years storage life at +20°C without charging, or until the Open Circuit Voltage (OCV) is <12.6V or <2.10Vpc, whichever occurs first. Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for dangerous Goods) and ICAO (International Civil Aviation Organisation).

## **Terminal Position**

# **Terminal Type SAE Terminals**







PDF Generated at https://eu.odysseybattery.com 21/04/2022 09:39:57 Information correct at time of exporting PDF. Please check website for updates.



EnerSysWorld Headquarters 2366Bernville Road Reading, PA 19605,USA Tel: +1-610-208-1991 / +1-800-538-3627

EH Europe GmbH Baarerstrasse 18 6300Zug.

EnerSys Asia 152 Beach Road Gateway East Building #11-08 Singapore 189721 Tel: +65 6508 1780