

ODP-AGM94R H7 L4 (94R-850 (LN4-H7))

Technical Data Sheet

Battery Type

AGM with Thin Plate Pure Lead (TPPL). Advanced dual-purpose battery for engine start and deep-cycle use

Power & Performance

Voltage	12V
Capacity (20-hour rate)	80Ah
Capacity (10-hour rate)	76Ah
Cold Cranking Amps (CCA, SAE J537)	840A
PHCA - 5-second pulse current	1500A
HCA	1200A
MCA	1000A
Reserve capacity	155 mins
Short circuit current (using IEC method)	2250A
Internal resistance at 20°C (using IEC method)	$5.7~\text{m}\Omega$

Dimensions & Weight

Length	315 mm
Width	175 mm
Height (to top of terminals)	188 mm
Height Container	191 mm
Weight	24.9 kg

Temperature

Operating Temperature Range	-40°C to +60°C
Optimum Storage Temperature	+20°C

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

Charging & self-discharge

Type of charging curve	100
Charge voltage @+20°C	14.4V to 14.8V
Self-discharge per month at +20°C	1.25%
Self-discharge per month at +40°C	5%

Fitting, handling & storage

Can be mounted or stored in any orientation except inverted. 2-years storage life at +20°C without charging, or until the Open Circuit Voltage (OCV) is <12.6V or <2.10Vpc, whichever occurs first. Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for dangerous Goods) and ICAO (International Civil Aviation Organisation).

PDF Generated at https://eu.odysseybattery.com 21/04/2022 12:49:00 Information correct at time of exporting PDF. Please check website for updates.




EnerSys World Headquarters 2366 Bernville Road Reading, PA 19605,USA Tel: +1-610-208-1991 / +1-800-538-3627 EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300Zug, Switzerland

EnerSys Asia 152 Beach Road Gateway East Building #11-08 Singapore 189721 Tel: +65 6508 1780


ODVSSEV Performance ACM THE TOTAL OF AGREED 175


Terminal Position



Terminal Type

SAE Terminals





ODP-AGM94R/H7/L4 RIGHT POSITIVE SAE TERMINALS