

TECHNICAL SPECIFICATIONS FOR RC9008



Radio Model	Motorola GP320/328/340/360, HT750/1250, GL2000, EX500, PRO5150/5550/7150/7450 GP328/338 Plus, GP344/388	
Battery Model	AM9008N, AM9008N-16, AM9009N, AM9009N-27, AM9012, AM9012-15, AM9013Li-17, HNN9008/9009/9012/9013	
<u>MECHANICAL CHARACTERISTICS</u>		
Dimension	115.8 X 114.2 X 50.1 mm	
Weight	Approx. 150g - without PSU	Approx. 680g - with PSU
Plastic Material	ABS+PC	
Charge Status Display	Single LED display	
<u>ELECTRICAL CHARACTERISTICS</u>		
Chemistry Supported	Ni-Cd, Ni-MH, Li-ion	
Input Voltage	15V	
Max. Charge Current	900mA	
Power Supply	External with safety approval	
AC Input	110V, 230V, and 240V	
Charge Time	1 ~ 3 hours depend on battery type	
Charge Mode	Ni-Cd / Ni-MH: Constant current Lithium Ion: Constant current to constant voltage	
Temperature	-5 ~ +40°C (+23 ~ +104°F)	
Agency Approval	CE for the charging unit	